



New Iseki SRA 800 & 950F Ride-on Brushcutters



The SRA 800 and 950F are ride-on brush cutters capable of cutting grass and thick vegetation right up to saplings. Their low height aids stability when used on slopes. Both machines are powered by Kawasaki electric start petrol engines – 16 hp & 24 hp respectively and have hydrostatic drive – 4WD for the SRA950F. Cutting widths are 80 cm or 95 cm.



Specifications

Model		SRA950F	SRA800		
Dimensions	Overall Length(mm)	1,965	1840		
	Overall Width(mm)	1,090	920		
	Overall Height(mm)	955	905		
	Ground Clearance(mm)	125	105		
	Wheelbase(mm)	1,320	1155		
	Tread(mm)	Front 830 Rear 785	Front 790	Rear 735	
Machine Mass(kg)		330	250		
Front Axle Mass(kg)		110	68		
Cutting System	Cutting Width(mm)	950	800		
	Blade Type	Free Knife x2, Knife Stay	←		
	Blade Fixation	Hard Lock Nut	←		
	Cutting Height(mm)	35~125(Stepless)	20~90(Stepless)		
	Work Capacity(a/h)	95	80		
	Driving System	V-Belt	←		
	Driving System	Speed	Forward(km/h)	0~10.0(without Sub Change)	Low 0~5.8 High 0~10
Rearward(km/h)			0~8.5(without Sub Change)	Low 0~3.5 High 0~6	
Tire		Front	4.00-7(φ400mm)	3.50-7(φ350mm)	
		Rear	17X8.00-8(φ440mm)	16X7.00-8(φ400mm)	
Driving System		On-Demand 4WD (F/R Wheels Hydraulic Drive)	←		
Handling Type		Handle with Knob	←		
Main Transmission		HST(13cc, with pump inside HST)	HST(10cc)		
Operation		Pedal, Lever	←		
Dif. Lock		Standard	←		
Brakes		Internally Expanding	←		
Minimum Turning Radius(mm)		2,100	1750		
Gradeability	25° or 46%	←			
Engine	Model	KAWASAKI FS691V	KAWASAKI FS481V		
	Maximum Output(PS)	24(Net: 20.9)	16(Net: 13.4)		
	Fuel Tank Capacity(L)	14 (with Fuel Gauge)	14 (with Fuel Gauge)		
Seat	F/R Adjustment(mm)	60	30		
	Reclining Adjustment	None	←		
	Cushion	None	←		
Equipment	"Eco Drive" mode lamp	Standard	None		
	Blade Cover	Right Side: Up & Down Flip Up Type	←		
	Dust Exhaust Fan	Standard	←		
	Cleaning of blade cover	Standard	←		
	Full open engine cover	Standard	Standard (engine portion)		
	Head Light	LED	None		
	Hour Meter	Standard	←		
	Engine Oil Warning Lamp	Standard	None		
	Battery	CCA:340A, V:12, Ah:24Ah	←		
	Protection frame	Option	←		



ISEKI UK & Ireland

3-5 Foxtail Road, Ransomes Europark, Ipswich IP3 9RT

Tel: 0044 (0) 1473 599266

www.iseki.co.uk

